CLAIMS

- 1 (Currently amended) A system for performing to perform Fast Fourier Transform (FFT) and Inverse Fast Fourier Transform (IFFT) operations, the system comprising:
- a first module for receiving to receive a plurality of inputs, said plurality of inputs being combined after a first multiplicands is are applied to each corresponding input;
- a first multiplicand generator for providing to provide said first multiplicands to said first module:
 - a first multiplier module for receiving to receive an output of said first module;
- a second multiplicand generator for providing to provide a second multiplicand to said first multiplier module, said second multiplicand being applied to said output of said first module by said first multiplier module:
- a second multiplier module for receiving to receive an output of said first multiplier module:
- a third multiplicand generator for providing to provide a third multiplicand to said second multiplier module, said third multiplicand being applied to said output of said first multiplier module by said second multiplier module;
- a third multiplier module for receiving to receive said output of said first multiplier module, said third multiplier module generating being configured to generate first and second outputs;
- a fourth multiplicand generator for providing to provide a fourth multiplicand to said third multiplier module, said fourth multiplicand being applied to said output of said first multiplier module by said third multiplier module to generate said first output of said third multiplier module, an image of said fourth multiplicand being applied to said output of said first multiplier module by said third multiplier module to generate said second output of said third multiplier module;
- a map module for receiving to receive outputs of said multiplier modules and for selecting and applying to apply multiplication factors to selected outputs of said multiplier modules, said map module having multiple outputs; and
- an accumulation module for receiving to receive each of said multiple outputs of said map module, said accumulation module performing being configured to perform an accumulation task for each of said multiple outputs of said map module, said accumulation module having multiple

outputs, where the multiple outputs of the accumulation module are one of an FFT and an IFFT of the plurality of inputs.

- (Original) A system according to claim 1 wherein said first multiplicand generator comprises a look-up table (LUT).
- (Original) A system according to claim 1 wherein said first multiplicand generator comprises a truth table.
- (Original) A system according to claim 1 wherein said first multiplicands are chosen from the set comprising +1, -1, +j or -j.
- (Original) A system according to claim 1 wherein said second multiplicand generator comprises a look-up table (LUT).
- 6. (Original) (Original) A system according to claim 1 wherein said third multiplicand is $e^{\frac{j \delta \pi}{2}}$.
- 7. (Original) A system according to claim 1 wherein said fourth multiplicand is $e^{\frac{d\pi}{32}}$
- 8. (Original) A system according to claim 1 wherein said image of said fourth $e^{\frac{J12\pi}{32}}.$ multiplicand is
- (Original) A system according to claim 1 wherein said multiplication factors
 applied by said map module to selected outputs of said multiplier modules is chosen from the set
 comprising +1, -1, +j or -j.
- 10. (Currently amended) A system for performing to perform an N-point FFT / IFFT operation, where N is the <u>an integer</u> number of the input samples, the system comprising:

 AMENDMENT PAGE 3 OF 10 Do. No. 9931-043

 SERIAL NO. 10/662.063

an input module for receiving to receive a plurality of inputs in parallel and for combining to combine said inputs after applying a multiplication factor to each of said inputs:

at least one multiplicand generator for providing to provide multiplicands to said system; at least two multiplier modules for performing to perform complex multiplications, at least one of said multiplier modules receiving being configured to receive an output of said input module, each of said multiplier modules receiving being configured to receive multiplicands from said at least one multiplicand generator, at least one of said multiplier modules receiving being configured to receive an output of another multiplier module;

a map module for receiving to receive outputs of all of said at least two multiplier modules, said map module selecting and applying to apply a multiplication factor to each of said outputs of said at least two multiplier modules, said map module generating being configured to generate multiple outputs; and

an accumulation module for receiving and accumulating to accumulate said multiple outputs of said map module, the accumulation module being configured to generate multiple outputs, where said multiple outputs of said accumulation module are one of an FFT and an IFFT of the plurality of inputs.

- 11. (Original) A system according to claim 10 wherein said at least two multiplier modules comprises $\frac{N}{32}$ + 1 multiplier modules.
- (Original) A system according to claim 10 wherein the N-point FFT / IFFT operation is completed in N clock cycles.
- 13. (Currently amended) A system according to claim 10 wherein said <u>multiple</u> <u>outputs of said</u> accumulation module generates <u>multiple outputs</u> corresponding to said multiple outputs received from said map module.
- (Original) A system according to claim 10 wherein said at least one multiplicand generator comprises at least one look-up table (LUT).

AMENDMENT PAGE 4 OF 10 DO, NO. 9931-043
SPERIAL NO. 10/662 063

- (Original) A system according to claim 10 wherein said at least one multiplicand generator comprises at least one truth table.
- (Currently amended) A system for performing Fast Fourier Transform / Inverse
 Fast Fourier Transform (FFT / IFFT) operations, the system comprising:
- a first summing module adapted to receive four inputs, said first summing module generating an output by combining said four inputs after applying a first set of multiplication factors to said four inputs;
- a first storage means for providing to provide said first set of multiplication factors to said first summing module;
- a first complex multiplier module adapted to receive said output of said first summing module;
- a first multiplicand generator for providing to provide a first multiplicand to said first complex multiplier module, said first multiplicand being applied to said output of said first summing module by said first complex multiplier module;
- a second complex multiplier module for receiving to receive an output of said first complex multiplier module;
- a second multiplicand generator for providing to provide a second multiplicand to said second complex multiplier module, said second multiplicand being applied to said output of said first complex multiplier module by said second multiplier module;
- a third complex multiplier module for receiving to receive said output of said first complex multiplier module, said third complex multiplier module generating to generate first and second outputs;
- a third multiplicand generator for providing to provide a third multiplicand to said third complex multiplier module, said third multiplicand being applied to said output of said first complex multiplier module by said third complex multiplier module to generate said first output of said third multiplier module, an image of said third multiplicand being applied to said output of said first complex multiplier module by said third complex multiplier module to generate said second output of said third complex multiplier module;

a map module for receiving to receive said outputs of said complex multiplier modules, said map module generating a plurality of outputs by selecting and applying a second set of multiplication factors to selected outputs of said complex multiplier modules; and

an accumulation module for receiving to receive said plurality of outputs from said map module, said accumulation module generating to generate a plurality of outputs by performing an accumulation task for each of said plurality of outputs from said map module, wherein said plurality of outputs of said accumulation module are one of an FFT and an IFFT of the four inputs.

- (Original) A system according to claim 16 wherein said first set of multiplication factors is chosen from the set comprising +1, -1, +j or -j.
- (Original) A system according to claim 16 wherein said first storage means comprises a look-up table (LUT).
- (Original) A system according to claim 16 wherein said first storage means comprises a truth table.
- (Original) A system according to claim 16 wherein said first multiplicand generator comprises a look-up table (LUT).
- (Original) A system according to claim 16 wherein first multiplicand generator comprises a truth table.
- 22. (Original) A system according to claim 16 wherein said second multiplicand is $e^{\frac{j8\pi}{32}}$
- 23. (Original) A system according to claim 16 wherein said third multiplicand is $e^{\frac{A\pi}{32}}$

- 24. (Original) A system according to claim 16 wherein said image of said third $j12\pi$ multiplicand is $e^{\frac{1}{32}}$
- 25. (Original) A system according to claim 13 wherein said second set of multiplication factors applied by said map module to selected outputs of said complex multiplier modules is chosen from the set comprising +1, -1, +j or -j.